

1. Unbox.

Inside the box you will have the following items:

- ✓ AIRCAP™ cover
 - ✓ 3 skirt sizes (3inch, 6inch, 9inch)
 - ✓ 2 way pump
 - ✓ Orange container which holds a valve tightening tool, instructions
 - ✓ 2 Patented AIRLOC™ Wedges
-

2. Inflate.

1. Lay the AIRCAP™ on a clean, flat surface with the color side facing up.
 2. Remove the valve cap by twisting it off to expose the red valve.
 3. Ensure the red valve is in the up position by pushing down on the spring
 4. Attach the pump hose by twisting it clockwise until it locks securely into place. Be sure the hose is connected to the "Inflate" port on the pump. Inflate each chamber to at least 5-7 PSI.
 5. Once all chambers are inflated, remove the pump hose and securely screw the valve caps back on.
 6. Place the AIRCAP™ on your hot tub with the thtml. logo positioned away/furthest from the side where you normally begin lifting the cover. This ensures the cover folds and operates as designed.
-

3. Zip.

- Once the AIRCAP™ is installed on your hot tub, it's time to select the correct skirt size.
 - Determine the amount of the hot tub's acrylic shell that remains exposed below the cover.
 - Your AIRCAP™ includes three skirt length options. Choose the size that completely covers the exposed acrylic for the best appearance and insulation.
 - Each skirt length includes two skirt panels. Simply zip the two panels onto the AIRCAP™, wrapping them around your hot tub.
 - That's it—your AIRCAP™ installation is complete, and you're ready to enjoy the benefits of your new cover!
-

Optional

The AIRCAP™ includes (2) of our patented AIRLOC™ Wedges, designed to help retain heat and improve your spa's energy efficiency. While they enhance performance, they are not required for the AIRCAP™ to function properly.

If you choose to use the wedges, attach one to each side of the cover using the included Velcro strips.

Important: Be sure to position the Velcro-attached wedges on the section of the cover that is folded back second when opening the spa. This ensures the wedges remain securely attached and are not pulled off during normal use.

When closing the cover for the first few times, you may need to apply a small amount of pressure to seat the cover into the wedges. This is completely normal. As the cover settles in, it will naturally conform to the wedges, making the fit easier over time.



Warranty Registration



AIRCAP

Scan QR code to register
your warranty.



Thank you for choosing the AIRCAP™ from thrml.™ We sincerely appreciate your business and are excited to be a part of your hot tub experience.

We hope you enjoy the performance, efficiency, and convenience of your new AIRCAP™.

Thank you for being a valued member of the thrml.™ family.

We'd love to hear your feedback.

feedback@thrmltech.com